

SP50 Series


Specialty Tools
Pneumatic Stapling Pliers

APACH
BUILDING FUTURES




CL Anvil


SP103020




SB5019



777



779



Features

- Powerful Shuttle Blade Provides Pre-Compression Prior to and During The Stapling Operating - Giving A Strong, Tight Closure Without Breaking The Corrugated Surface
- 6" x 1" High Throat Allows Flexibility of Staple Placement and Limits Interference from Obstacles Such As Box Flanges
- C Anvils (CL or CR Available for Sealing Partial Overlap Cartons)
- Penetrates and Securely Fastens up to 2 Thicknesses of Double - Wall:
2x AB Flute or 4x C Flute Boards
(A Flute = 3/16" or 4.8 mm Thick)
(B Flute = 1/8" or 3.2 mm Thick)
(C Flute = 5/32" or 4.0 mm Thick)

Fasteners

Tools	Staple Type	Similar to	Crown Size	Shank Diameter	Leg Length	Load Capacity
SP50-10B-A	SB 103020	Bostitch SB 103020	12.95 mm 1/2"	0.50 x 2.60 mm .020 x .103"	10, 12, 15 mm 3/8, 1/2, 5/8"	102
SP50-5B-A	SB 5019	Bostitch SB 5019	12.85 mm 1/2"	0.48 x 1.25 mm .019 x .050"	6, 10, 12, 15 mm 1/4, 3/8, 1/2, 5/8"	108
SP50-777-A	777	JK 777	12.3 mm 1/2"	0.65 x 2.25 mm .026 x .090"	10, 12, 15 mm 3/8, 1/2, 5/8"	140
SP50-779-A	779	JK 779	12.3 mm 1/2"	0.63 x 1.3 mm .025 x .050"	8, 10, 12, 14, 16 mm 5/16, 3/8, 1/2, 9/16, 5/8"	125

Applications

- Corrugated Containers
- Trays & Lids
- End Caps
- Headers & Bags
- Container Inserts
- Bedding

Tool Specifications

Weight	Dimensions (L x W x H)	Operating Pressure
2.2 kg	370 x 55 x 240 mm	2.5 - 3.9 kg / cm ²
4.8 lbs	14 1/2 x 2 1/8 x 9 1/2"	36 - 55 psi

APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41280
Tel +886 4 2491 5576 Fax +886 4 2491 5580
www.apach.com.tw

