

AW150A

3/4" Lightly Composite Air Impact Wrench



Features

- Mechanism: Twin Hammer
- Composite and magnesium material
- Highest durable Japanese steel anvil
- Handle exhaust
- Forward: 3 positions; Reverse: 1 position
- Nut-Busting Torque **1,600 ft-lb/ 2250 Nm**
- The cylinder is using material of FCD45 and has special heat treat, it has high wear resistance
- Blade with spring mounted, make sure the blades can be opened when working
- Simple structure, easy to service and repair

Applications



Automotive



Boat



Industry
Assembling Line

Tool Specifications • 6 Pcs/20 Kg/21 Kg/1.3'

Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Torque 5 Sec.	Max Torque 10 Sec.	Free Speed	Vibration	Sound Pressure Level	Overall Length	Net Weight
3/4"	1-1/4"	7.0 CFM	3/8"	6.2 Bar	3/8"	1200 FT-LB	1500 FT-LB	6000 RPM	9.6 m/s ²	96.5 DbA	209 mm	3.0 kg
	M32	198 L/Min		90 psi		1687 N.m.	2108 N.m.				8-1/4"	6.4 LB

APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208

Tel +886 4 2271 2835 Fax +886 4 2271 4840

www.apach-tools.com info@apach.com.tw

